



Siro **2026**
LED
Strips & Strings



Hi-Light Lighting

www.hilight-lighting.com




Xiamen Headquarters 50acres



Zhangzhou factory 210acres



Thailand factory 70acres



- **SiroBuildex,** founded in 2001, is a national high-tech enterprise, specialized in LED lighting for over 20 years. Headquartered in Xiamen, China, we have three manufacturing bases located in Xiamen and Zhangzhou of China, and Chonburi of Thailand, covering a total area of over 300 acres and nearly 300,000 square meters of production workshops, office buildings, R&D centers and CNAS national standard laboratory. Throughout all these years, we have built an industrial chain integrating innovative research and development, intelligent manufacturing and intelligent lighting solution output. With more than 2,000 employees and a monthly production capacity of over 20 million pieces, we have established long-term and stable cooperative relations with mainstream supermarkets and brands in North America, Europe and Asia-Pacific.

- **Highly-qualified Products**

With our rich ODM/OEM experience and proven performance, we are currently a prominent partner of many world famous lighting brands and large international chain stores. We have customers enjoying our products and service over 60 countries and we are one of the main suppliers of LED, CFL and other lighting products in US market.

- **One-Stop Products Selection**

We have developed a full range of LED lighting products from light bulbs to lighting fixtures, covering over a thousand models, which can meet the demands of different markets around the world. We are confident to provide customers with one-stop LED solutions with accredited quality, capacity and variety.

- **Quality Certification**

As a dual-system certified enterprise (ISO9001, ISO14001), we have established access thresholds covering the global mainstream markets:

- ✓ Safety Certification: UL/CUL/ETL/CE/GS-LVD/PSE
- ✓ Energy Efficiency Certification: ENERGY STAR/DLC/EUP/MEPS
- ✓ Regional Certification: CCC/CQC/KC/SAA/C-Tick
- ✓ Professional Certification: CB/ENEC/NOM/PROCELL

Relying on the intelligent manufacturing system and the CNAS standard laboratory, we ensure that each product complies with the technical specifications of various countries. We have now achieved barrier-free access to major lighting markets such as Europe, America, Asia-Pacific, and Latin America.

Contents

Strip Light (bare tape)	01~07
Strip Light (dipped tape)	08~11
Strip Light (sleeved tape)	12~13
Ultrathin COB Strip Light	14
COB Strip Light	15~19
Neon Flex	20~21
Neon Flex Side View	22
Neon Flex Multiple-side View	23
Neon Flex 360deg View	24
Neon Flex shapeable	25~26
Special Flexible Super Thin Neon Flex	27
PVC Strip Light	28
Wall Washer Strip Light	29
Camera TV Strip Light	30
HDMI TV Strip Light	31
Grow Strip Light	32
Ultrathin Chasing Color Strip Light	33
High-voltage input Tape Light	34
High-voltage input COB Light	35
High-voltage input Rope Light	36
High-voltage input Neon COB	37~38
Christmas String Light	39
Curtain String Light	40
String Light	41
Camping String Light	42
Fairy String Light	43
Smart String Light	44
Black Translucent String Light	45
Solar String Light	46
Classic String Light	47
Indoor String Light	48

Strip Light (bare tape)



Features

- High quality driver with minimized flickering.
- Flexible and linkable.
- Cuttable, dimmable & safe using low voltage power.
- Widely used in bar, kitchen, shower room, classroom, party, bedroom, kitchen, living room etc.
- Bare tape light without coating or cover.



Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLED-TAPE-12W	SMD	3000K	12	12W/M	529Lm/M	80	12V 1A	RF control	/	100mm	3M tape Clip	5000x10x3mm
HLLED-TAPE-30W	SMD	3000K	24	30W/M	2685Lm/M	80	24V 1.5A	/	/	125mm	3M tape Clip	5000x10x3mm
HLLED-TAPE-12W-CW	SMD	2700K~6500K	12	12W/M	1000Lm/M	80	12V 1A	PIR	/	100mm	3M tape Clip	5000x10x3mm
HLLED-TAPE-36W-CW-A	SMD	2700K~6500K	24	36W/M	2835Lm/M	80	24V 1.5A	RF control	/	125mm	3M tape Clip	5000x10x3mm
HLLED-TAPE-36W-CW-B	SMD	2700K~6500K	24	36W/M	2950Lm/M	80	24V 1.5A	RF control	IP20	100mm	3M tape Clip	5000x10x3mm
HLLED-TAPE-60W-CW	SMD	2700K~6500K	24	60W/M	4900Lm/M	80	24V 2.5A	RF control	/	100mm	3M tape Clip	5000x10x3mm

Strip Light (bare tape)




Features

- High quality driver with minimized flickering.
- Flexible and linkable.
- Cuttable, dimmable & safe using low voltage power.
- MULTIPLE CHOICES- RGB or RGB+W LED strip lights support multi-colors that can control the light color, the intensity and settings of custom flashes, strobe, cast iron and flash colors via remote, which will create colorful world for you.
- Widely used in bar, kitchen, shower room, classroom, party, bedroom, kitchen, living room etc.
- Smart control or remote control are available.



Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLED-TAPE-12W-RGB	SMD	RGB	24	12W/M	/	/	24V 0.5A	RF control	IP20	100mm	3M tape Clip	5000x12x3mm
HLLED-TAPE-12W-RGBW	SMD	RGBW	24	12W/M	600	80	24V 0.5A	RF control	IP20	100mm	3M tape Clip	5000x12x3mm
HLLED-TAPE-12W-RGBCW	SMD	RGBCW	24	12W/M	600	80	24V 0.5A	RF control	IP20	100mm	3M tape Clip	5000x12x3mm

Strip Light (bare tape)



Features

- Built in IC for color chasing effect.
- High quality driver with minimized flickering.
- Flexible and linkable.
- Cuttable, dimmable & safe using low voltage power
- Smart RGBIC Effects: RGBIC LED strip lights present stunning segmented colors on a line. It is designed for holiday create a colorful lighting feast to your Halloween decorations and party decor.
- Widely used in bar, kitchen, shower room, classroom, party, bedroom, kitchen, living room etc.
- Smart control or remote control are available.



Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLED-TAPE-24W-RGBIC	SMD	RGBIC	24	24W/M	/	/	24V 1.2A	RF control	IP20	100mm	3M tape Clip	5000x12x4mm
HLLED-TAPE-24W-RGBWIC	SMD	RGBWIC	24	24W/M	/	/	24V 1.2A	RF control	IP20	100mm	3M tape Clip	5000x12x4mm
HLLED-TAPE-24W-RGBCWIC	SMD	RGBCWIC	24	24W/M	/	/	24V 1.2A	RF control	IP20	100mm	3M tape Clip	5000x12x4mm

Strip Light (bare tape)



Features

- High quality driver with minimized flickering.
- Flexible and linkable.
- Cuttable, dimmable & safe using low voltage power.
- MULTIPLE CHOICES-RGBCW LED strip lights support monochrome or multi-colors. We can control the light color, the intensity and settings of custom flashes, strobe, cast iron and flash colors via remote. They will create a colorful world for you.
- Widely used in bar, kitchen, shower room, classroom, party, bedroom, kitchen, living room etc.



Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLED-TAPE-12W-RGB	SMD	RGB	24	12W/M	/	/	24V 0.5A	RF control	IP20	100mm	3M tape Clip	5000x12x4mm
HLLED-TAPE-12W-RGBW-A	SMD	3000K RGB	12	12W/M	529Lm/M	80	12V 1A	RF control	/	100mm	3M tape Clip	5000x12x4mm
HLLED-TAPE-12W-RGBW-B	SMD	3000K RGB	12	12W/M	1000Lm/M	80	12V 1A	PIR	/	100mm	3M tape Clip	5000x12x4mm
HLLED-TAPE-24W-RGBW	SMD	3000K RGB	24	24W/M	1535Lm/M	80	24V 1A	RF control	/	125mm	3M tape Clip	5000x12x4mm
HLLED-TAPE-7.2W-RGBCW	SMD	1800K~6500K RGB	24	7.2W/M	500Lm/M	80/90	24V 1.5A	WiFi, Remote control, Wire control	IP20	100mm	3M tape Clip	5000x12x4mm
HLLED-TAPE-36W-RGBCW	SMD	2700K~5000K RGB	24	36W/M	2950Lm/M	80	24V 1.5A	RF control	IP20	100mm	3M tape Clip	5000x12x4mm

Strip Light (bare tape)



Features

- High quality driver with minimized flickering
- Flexible and linkable.
- Cuttable, dimmable & safe using low voltage power
- Widely used in bar, kitchen, shower room, classroom, party, bedroom, kitchen, living room etc.



50,000
HOURS

CRI
80Ra to 90Ra


Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLED-TAPE-8W	SMD	RGB~3000K	12V	8W	529	80	12V 1A	RF control	γ	100mm	3M tape Clip	0.3m*10x2mm

Strip Light (bare tape)



Features

- DIY your desired shape.
 - High quality driver with minimized flickering.
 - Cuttable, dimmable & safe using low voltage power.
- Wide application: in bar, kitchen, shower room, class-room, party, bedroom, kitchen, living room etc.
- Cuttable and linkable.



Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HILLED-TAPE-30W	SMD	3000K	24V	30W	2685	80	24V 1.5A	/	/	125mm	3M tape Clip	5000x8x2mm

Strip Light (bare tape)



Features

- DIY your desired shape.
- High quality driver with minimized flickering.
- RF control.
- Color Changing: RGB+3000K/RGB+2700~6500K. RGB+CW colors are available.
- Cuttable and linkable.
- Easy Installation & Sticky Tape: 3M adhesive and mounting brackets/fixing clips.
- Wide application: kitchen, shower room, classroom, party, bedroom, kitchen, living room etc.



50,000
HOURS

CRI
80Ra to 90Ra

Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLED-TAPE-36W	SMD	2700K~6500K	24V	36W	2835	80	24V 1.5A	RF control	I	125mm	3M tape Clip	5000x8x2mm
HLLED-TAPE-21W-RGBW	SMD	RGB~3000K	24V	21W	1535	80	24V 1A	RF control	f	250mm	3M tape Clip	5000x10x2mm
HLLED-TAPE-21W-RGBW	SMD	RGB 2700K~6500K	24V	21W	1535	80	24V 1A	RF control	f	250mm	3M tape Clip	5000x10x2mm

Strip Light (dipped tape)



Features

- 24 volt LED power supply required (sold separately).
- High quality driver with minimized flickering.
- Easy installation: Simply peel and stick the 3M adhesive backing for a long lasting, permanent hold.
- Customizable: Cut and reconnect tape light for custom lengths and configurations.



Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLED-TAPE-30W-R-GBW	SMD	RGB~3500K	24V	30W	2100	80	24V 1.25A	WiFi	IP20	0.25M	3M tape Clip	5000x12x4mm

Strip Light (dipped tape)



Features

- USB DC5V power supply (sold separately).
- High quality driver with minimized flickering.
- Easy installation: Simply peel and stick the 3M adhesive backing for a long lasting, permanent hold.
- Customizable: Cut and reconnect tape light for custom lengths and configurations.
- With IR or RF remote control.



Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLED-TAPE-USB	SMD	RGBW	5V	10~15W	500~800	80	USB DC5V	Remote	IP20	0.25M	3M tape Clip	3000x10x3mm

Strip Light (dipped tape)



Features

- High quality driver with minimized flickering.
- Flexible and linkable.
- Cuttable, dimmable & safe using low voltage power.
- Widely used in bar, kitchen, shower room, classroom, party, bedroom, kitchen, living room etc.
- Easy installation: Simply peel and stick the 3M adhesive backing for a long lasting, permanent hold.



Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLED-TAPE-12W	SMD	3000K	12	12W/M	529Lm/M	80	12V 1A	RF control	/	100mm	3M tape Clip	300x10x3mm
HLLED-TAPE-30W	SMD	3000K	24	30W/M	2685Lm/M	80	24V 1.5A	/	/	125mm	3M tape Clip	5000x10x3mm
HLLED-TAPE-12W-CW	SMD	2700K~6500K	12	12W/M	1000Lm/M	80	12V 1A	PIR	/	100mm	3M tape Clip	5000x10x3mm
HLLED-TAPE-36W-CW-A	SMD	2700K~6500K	24	36W/M	2835Lm/M	80	24V 1.5A	RF control	/	125mm	3M tape Clip	5000x10x3mm
HLLED-TAPE-36W-CW-B	SMD	2700K~6500K	24	36W/M	2950Lm/M	80	24V 1.5A	RF control	IP20	100mm	3M tape Clip	5000x10x3mm
HLLED-TAPE-60W-CW	SMD	2700K~6500K	24	60W/M	4900Lm/M	80	24V 2.5A	RF control	/	100mm	3M tape Clip	2500x10x3mm
HLLED-TAPE-12W-RGB	SMD	RGB	24	12W/M	/	/	24V 0.5A	RF control	IP20	100mm	3M tape Clip	5000x10x3mm
HLLED-TAPE-24W-RGB	SMD	RGB	24	24W/M	/	/	24V 1.2A	RF control	IP20	100mm	3M tape Clip	2500x10x3mm

Strip Light (dipped tape)




Features

- Built-in IC for color chasing effect.
- High quality driver with minimized flickering.
- Flexible
- Cuttable, dimmable & safe using low voltage power.
- Smart RGBIC Effects: RGBIC LED strip lights present stunning segmented colors on a line. It is designed for holiday create a colorful lighting feast to your Halloween decorations and party decor.
- Widely used in bar, kitchen, shower room, classroom, party, bedroom, kitchen, living room etc.



Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLED-TAPE-12W-RGB	SMD	RGB	24	12W/M	/	/	24V 0.5A	RF control	IP20	100mm	3M tape Clip	5000x12x3mm
HLLED-TAPE-12W-RGBW-A	SMD	3000K RGB	12	12W/M	529Lm/M	80	12V 1A	RF control	/	100mm	3M tape Clip	300x12x3mm
HLLED-TAPE-12W-RGBW-B	SMD	3000K RGB	12	12W/M	1000Lm/M	80	12V 1A	PIR	/	100mm	3M tape Clip	5000x12x3mm
HLLED-TAPE-24W-RGBW	SMD	3000K RGB	24	24W/M	1535Lm/M	80	24V 1A	RF control	/	125mm	3M tape Clip	5000x12x3mm
HLLED-TAPE-7.2W-RGBCW-A	SMD	1800K~6500K RGB	24	7.2W/M	500Lm/M	80/90	24V 1.5A	WiFi, Remote control, Wire control	IP20	100mm	3M tape Clip	5000x12x3mm
HLLED-TAPE-36W-RGBCW	SMD	2700K~5000K RGB	24	36W/M	2950Lm/M	80	24V 1.5A	RF control	IP20	100mm	3M tape Clip	5000x12x3mm
HLLED-TAPE-7.2W-RGBCW-B	SMD	1800K~6500K RGB	24	7.2W/M	500Lm/M	80/90	5000	WiFi, Remote control, Wire control	IP44	100mm	3M tape Clip	5000x12x3mm
HLLED-TAPE-24W-RGBIC	SMD	RGBIC	24	24W/M	/	/	24V 1.2A	RF control	IP20	100mm	3M tape Clip	2500x12x3mm
HLLED-TAPE-24W-RGBWIC	SMD	RGBWIC	24	24W/M	/	/	24V 1.2A	RF control	IP20	100mm	3M tape Clip	2500x12x3mm
HLLED-TAPE-24W-RGBCWIC	SMD	RGBCWIC	24	24W/M	/	/	24V 1.2A	RF control	IP20	100mm	3M tape Clip	2500x12x3mm

Strip Light (sleeved tape)



Features

- High quality driver with minimized flickering
- Flexible and linkable
- Cuttable, dimmable & safe using low voltage power
- MULTIPLE CHOICES- RGB LED strip lights support multi-colors. We can control the light color, the intensity and settings of custom flashes, strobe, cast iron and flash colors via remote. They will create a colorful world for you.
- Widely used in bar, kitchen, shower room, classroom, party, bedroom, kitchen, living room etc.



Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLED-TAPE-12W	SMD	3000K	12	12W/M	529Lm/M	80	12V 1A	RF control	/	100mm	3M tape Clip	300x12x4mm
HLLED- TAPE-30W	SMD	3000K	24	30W/M	2685Lm/M	80	24V 1.5A	/	/	125mm	3M tape Clip	5000x12x4mm
HLLED- TAPE-12W-CW	SMD	2700K~5000K	12	12W/M	1000Lm/M	80	12V 1A	PIR	/	100mm	3M tape Clip	5000x12x4mm
HLLED- TAPE-36W-CW-A	SMD	2700K~5000K	24	36W/M	2835Lm/M	80	24V 1.5A	RF control	/	125mm	3M tape Clip	5000x12x4mm
HLLED- TAPE-36W-CW-B	SMD	2700K~5000K	24	36W/M	2950Lm/M	80	24V 1.5A	RF control	IP20	100mm	3M tape Clip	5000x12x4mm
HLLED- TAPE-60W-CW	SMD	2700K~5000K	24	60W/M	4900Lm/M	80	24V 2.5A	RF control	/	100mm	3M tape Clip	2500x12x4mm
HLLED- TAPE-12W-RGB	SMD	RGB	24	12W/M	/	/	24V 0.5A	RF control	IP20	100mm	3M tape Clip	5000x12x4mm
HLLED- TAPE-24W-RGB	SMD	RGB	24	24W/M	/	/	24V 1.2A	RF control	IP20	100mm	3M tape Clip	5000x12x4mm

Strip Light (sleeved tape)




Features

- High quality driver with minimized flickering.
- Flexible and linkable.
- Cuttable, dimmable & safe using low voltage power.
- Widely used in bar, kitchen, shower room, classroom, party, bedroom, kitchen, living room etc.



Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLED-TAPE-12W-RGB	SMD	RGB	24	12W/M	/	/	24V 0.5A	RF control	IP20	100mm	3M tape Clip	5000x12x3mm
HLLED-TAPE-12W-RGBW-A	SMD	3000K RGB	12	12W/M	529Lm/M	80	12V 1A	RF control	/	100mm	3M tape Clip	300x12x3mm
HLLED-TAPE-12W-RGBW-B	SMD	3000K RGB	12	12W/M	1000Lm/M	80	12V 1A	PIR	/	100mm	3M tape Clip	5000x12x3mm
HLLED-TAPE-24W-RGBW	SMD	3000K RGB	24	24W/M	1535Lm/M	80	24V 1A	RF control	/	125mm	3M tape Clip	5000x12x3mm
HLLED-TAPE-7.2W-RGBCW	SMD	1800K~6500K RGB	24	7.2W/M	500Lm/M	80/90	24V 1.5A	WiFi, Remote control, Wire control	IP20	100mm	3M tape Clip	5000x12x3mm
HLLED-TAPE-36W-RGBCW	SMD	2700K~5000K RGB	24	36W/M	2950Lm/M	80	24V 1.5A	RF control	IP20	100mm	3M tape Clip	5000x12x3mm
HLLED-TAPE-7.2W-RGBCW	SMD	1800K~6500K RGB	24	7.2W/M	500Lm/M	80/90	2.4V 1.5A	WiFi, Remote control, Wire control	IP44	100mm	3M tape Clip	5000x12x3mm
HLLED-TAPE-24W-RGBIC	SMD	RGBIC	24	24W/M	/	/	24V 1.2A	RF control	IP20	100mm	3M tape Clip	2500x12x3mm
HLLED-TAPE-24W-RGBWIC	SMD	RGBWIC	24	24W/M	/	/	24V 1.2A	RF control	IP20	100mm	3M tape Clip	2500x12x3mm
HLLED-TAPE-24W-RGBCWIC	SMD	RGBCWIC	24	24W/M	/	/	24V 1.2A	RF control	IP20	100mm	3M tape Clip	2500x12x3mm

Ultrathin COB Strip Light



Features

- Slim profile with.
- Mini Wide Size 3mm.
- Min.Bending Diameter: $\phi 60\text{mm}$.
- High quality FPC.
- Different color temperatures are available for selection.
- FPC board connection without soldering.
- White coating is available.



Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLEO-COB-8W-A	COB	3000K 4000K 6500K	24V	8W	700	90	DC24V	RF control	IP20	20MM	3M tape	5000*3*1.6mm

COB Strip Light(white)



Features

- With white or yellow silicon coating.
- Edgelit technology to provide great lighting.
- Super super even lighting performance with no dark spots. Replace traditional SMD LED strip lights, providing higher brightness lighting!
- Ultra-long continuous length can be connectable to satisfy you to decorate large spaces.
- Dimmable & Multifunctional: compatible with triac dimmers and RF/IR remote.
- Easy to DIY: cuttable and connectable. The cut strip light can also be reconnected, which is very convenient for DIY!
- Different coatings are available.



Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLED-COB-40W	COB	3000K	24	40W/M	2950Lm/M	80	24V 2A	RF control	IP20	20mm	3M tape Clip	5000x10x3mm
HLLED-COB-10W	COB	3000K	5	10W/M	200Lm/M	80	5V 2A	RF control	IP20	20mm	3M tape Clip	3000x10x3mm
HLLED-COB-10W-CW	COB	2700K~5000K	5	10W/M	200Lm/M	80	5V 2A	RF control	IP20	20mm	3M tape Clip	3000x10x3mm
HLLED-COB-36W-A	COB	3000K	24	36W/M	2950Lm/M	90	24V 1.5A	RF control	IP20	20mm	3M tape Clip	5000x10x3mm
HLLED-COB-36W-B	COB	4000K	24	36W/M	2950Lm/M	90	24V 1.5A	RF control	IP20	20mm	3M tape Clip	5000x10x3mm
HLLED-COB-36W-CW	COB	2700K~5000K	24	36W/M	2950Lm/M	90	24V 1.5A	RF control	IP20	20mm	3M tape Clip	5000x10x3mm
HLLED-COB-24W-CW	COB	2700K~6500K	24	24W/M	2500Lm/M	90	24V 1A	RF control	IP20	20mm	3M tape Clip	3000x10x3mm
HLLED-COB-40W	COB	3000K	24	40W/M	2950Lm/M	80	24V 1.5A	2.4G RF	IP20	50MM	3M tape Clip	5000x5x3mm
HLLED-COB-36W	COB	RGBCW	24	36W/M	2950Lm/M	80	24V 1.5A	2.4G RF	IP20	50MM	3M tape Clip	5000x5x3mm
HLLED-COB-20W-RGB	COB	RGB	24	20W/M	1000Lm/M	/	24V 1.5A	RF control	IP20	50MM	double-sided tape	5000x12x3mm

COB Strip Light



Features

- The rgb color flowing striplight has a built-in ic chip that allows multiple colors to be displayed in a single line at the same time.
- Ultra-long continuous length can be connectable to satisfy you to decorate large spaces.
- Dimmable & Multifunctional: compatible with triac dimmers and RF/IR remote.
- Easy to DIY: cuttable and connectable. The cut strip light can also be reconnected, which is very convenient for DIY!
- Different coatings are available.
- Wifi smart control or remote control is available.
- White coating is available.



Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLED-COB-24W-RGB	COB	RGB	24	24W/M	/	/	24V 1A	RF control	IP20	20mm	3M tape Clip	3000x12x3mm
HLLED-COB-60W-RGB	COB	RGB	24	60W/M	/	/	24V 2.5A	RF control	IP20	20mm	3M tape Clip	5000x12x3mm
HLLED-COB-24W-RGBIC	COB	RGBIC	24	24W/M	/	/	24V 1A	RF control	IP20	20mm	3M tape Clip	5000x12x3mm
HLLED-COB-24W-RGBWIC	COB	RGBWIC	24	24W/M	/	/	24V 1A	RF control	IP20	20mm	3M tape Clip	5000x12x3mm

COB Strip Light




Features

- 5V USB powered.
- Super even lighting performance with no dark spots.
Replace traditional SMD LED strip lights, providing higher brightness lighting!
- Ultra-long continuous length can be connectable to satisfy you to decorate large spaces.
- Dimmable & Multifunctional: compatible with triac dimmers and RF/IR remote.
- Easy to DIY: cuttable and connectable. The cut strip light can also be reconnected, which is very convenient for DIY!
- Different coatings are available.



Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLED-COB-10 W-RGBW	COB	RGB	5	10W/M	200Lm/M	80	5V 2A	RF control	IP20	20mm	3M tape Clip	3000x8x3mm
HLLED-COB-60W-RGBW	COB	3000K+ RGB	5	60W/M	2950Lm/M	90	24V 2.5A	RF control	IP20	20mm	3M tape Clip	3000x8x3mm
HLLED-COB-8W-RGBCW-A	COB	1800K~6500K RGB	5	8W/M	720Lm/M	80/90	/	WiFi, Remote control, Wire control	IP20	20mm	3M tape Clip	3000x8x3mm

COB Strip Light



Features

- Motion Sensor Strip Light: In motion sensor mode, it lights up as soon as it detects motion within 10 ft, and automatically turns off if no motion is detected.
- Day & Night 2 Sensor Modes: Day Mode ☀ means the Light up as long as triggered by the motion; Night Mode ☒ means only light up triggered by the motion in the dark.
- Easy to Install: 3M adhesive can be easily pasted on a smooth surface. The battery box have magnetic strip and comes with 3M double-sided adhesive, which is applicable anywhere.
- Widely Used: It can be widely used in stairs, bedroom, under bed lights, under cabinet lights, kitchen, hallway, around walls, computer lighting, TV back lights, counter lighting, closet lighting, shelf lighting, etc.





50,000
HOURS

CRI
≥80Ra or >90Ra

Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLED-COB-10W-A	COB	3000K	5V	10W	350	80	5V 2A	RF control	IP20	20mm	3M tape Clip	1mx8mmx3mm
HLLED-COB-10W-B	COB	2700K~5000K	5V	10W	350	80	5V 2A	RF control	IP20	50mm	3M tape Clip	1mx10mmx3mm
HLLED-COB-10W-C	COB	3000K	5V	10W	350	80	5V 2A	RF control	IP20	50mm	3M tape Clip	1mx8mmx3mm
HLLED-COB-10W-D	COB	2700K~5000K	5V	10W	350	80	5V 2A	RF control	IP20	50mm	3M tape Clip	1mx10mmx3mm
HLLED-COB-10W-RGB	COB	3000K~RGB	5V	10W	350	80	5V 2A	RF control	IP20	50mm	3M tape Clip	1mx10mmx3mm

COB Strip Light



Features


- Super Brightness with COB pad design.
- Wide Size 15mm & 30mm.
- Min.Bending Diameter: $\Phi 60\text{mm}$.
- High quality FPC.
- Different color temperature segments are available for selection

When using LEDs trips,the twising angle within a 0.5-meter section should not exceed 180°



Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLED-COB-24W-A	COB	3000K 4000K 6500K	24V	24W/M	2640	90	DC24V	RF control	IP20	50mm	3M tape	5000*15*1.5mm
HLLED-COB-44W-B	COB	3000K 4000K 6500K	24V	44W/M	4400	90	DC24V	RF control	IP20	25MM	3M tape	5000*30*1.4mm

Neon Flex




Features

- Different size at 6X12mm, 8x17mm, 10x10mm are available.
- Bright Premium Lighting & Energy Saving: pure and uniform lighting without spots or dark dots.
- Durable & Eco-friendly, cuttable and bendable for any shapes you want.
- IP65 waterproof design.
- Widely Application: suitable for decorating your home, bedroom, bathroom, car trunk, marine, exterior, boat, trucks, motorcycle, tv, desk, mirror, pool, etc.
- Remote or App-controlled, addressable LEDs were designed for extraordinary brightness and color quality in over 16 million colors.
- 12V or 24V neon flex are available.



Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLED-NE-48W-RGB	SMD	RGB	24	18W-48W	/	80	24V 2A	WIFI/RF	IP65	/	3M tape Clips	5000x6mmx12mm
HLLED-NE-48W-RGBIC	SMD	RGBIC	24	18W-48W	/	80	24V 2A	WIFI/RF	IP65	/	3M tape Clips	5000x6mmx12mm
HLLED-NE-48W-RGB	SMD	RGB	24	18W-48W	/	80	24V 2A	WIFI/RF	IP65	/	3M tape Clips	5000x8mmx17mm
HLLED-NE-48W-RGBW	SMD	RGBW	24	18W-48W	/	80	24V 2A	WIFI/RF	IP65	/	3M tape Clips	5000x8mmx17mm
HLLED-NE-48W-RGBICW	SMD	RGBICW	24	18W-48W	/	80	24V 2A	WIFI/RF	IP65	/	3M tape Clips	5000x8mmx17mm
HLLED-NE-48W-RGB	SMD	RGB	24	18W-48W	/	80	24V 2A	WIFI/RF	IP65	/	3M tape Clips	5000x10mmx10mm
HLLED-NE-48W-RGBICW	SMD	RGBIC	24	18W-48W	/	80	24V 2A	WIFI/RF	IP65	/	3M tape Clips	5000x10mmx10mm

Neon Flex



Features

- Different size at 12X06mm , 12X20mm are available.
- Bright Premium Lighting & Energy Saving: pure and uniform lighting without spots or dark dots.
- Durable & Eco-friendly, cuttable and bendable for any shapes you want.
- IP65/68 waterproof design.
- Widely Application: suitable for decorating your home, bedroom, bathroom, car frunk, marine, exterior, boat, trucks, motorcycle, tv, desk, mirror, pool, etc.
- App-controlled, addressable LEDs were designed for extraordinary brightness and color quality in over 16 million colors.




Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLED-NE-48W-RGB	SMD	RGB	24	18W-48W	/	80	24V 2A	WIFI/RF	IP65/68	/	3M tape Clips	5000x12x20mm
HLLED-NE-48W-RGBW	SMD	RGBW	24	18W-48W	/	80	24V 2A	WIFI/RF	IP65/68	/	3M tape Clips	5000x12x20mm
HLLED-NE-48W-RGBICW	SMD	RGBICW	24	18W-48W	/	80	24V 2A	WIFI/RF	IP65/68	/	3M tape Clips	5000x12x20mm
HLLED-NE-23W-RGBW	COB	RGBW	24	23W	630	90	DC24V	RF	IP65/68	/	3M tape Clips	5000*12*06mm

Neon Flex Side View



Features


- Lighting at side.
- Bright Premium Lighting & Energy Saving: pure and uniform lighting without spots or dark dots.
- Durable & Eco-friendly, cuttable and bendable for any shapes you want.
- IP65/68 waterproof design.
- Widely Application: suitable for decorating your home, bedroom, bathroom, car frunk, marine, exterior, boat, trucks, motorcycle, tv, desk, mirror, pool, etc.
- App-controlled, addressable LEDs were designed for extraordinary brightness and color quality in over 16 million colors.
- 12V or 24V neon flex are available.



Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLD-NE-48W-RGBW	SMD	RGBW	24	18W-48W	/	80	24V 2A	WIFI/RF	IP65/68	/	3M tape Clips	5000x12x20mm



Neon Flex

Multiple-side View



Features

- Lighting in 3 sides with 4-way bendable.
- Bright Premium Lighting & Energy Saving: pure and uniform lighting without spots or dark dots.
- Durable & Eco-friendly, cuttable and bendable for any shapes you want.
- IP65 waterproof design.
- Widely Application: suitable for decorating your home, bedroom, bathroom, car trunk, marine, exterior, boat, trucks, motorcycle, tv, desk, mirror, pool, etc
- App-controlled, addressable LEDs were designed for extraordinary brightness and color quality in over 16 million colors.



Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLED-NE-48W-RGBW	SMD	RGBW	24	18W-48W	/	80	24V 2A	WIFI/RF	IP65	/	3M tape Clips	5000x16x16mm

Neon Flex

360deg View



Features

- Lighting in 360°
- Bright Premium Lighting & Energy Saving: pure and uniform lighting without spots or dark dots.
- Durable & Eco-friendly, cuttable and bendable for any shapes you want.
- IP65/68 waterproof design.
- Widely Application: suitable for decorating your home, bedroom, bathroom, car frunk, marine, exterior, boat, trucks, motorcycle, tv, desk, mirror, pool, etc.
- App-controlled, addressable LEDs were designed for extraordinary brightness and color quality in over 16 million colors.



Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLED-NE-60W-RGB	SMD	RGB	24	60W	2000	80	24V 2A	WIFI/RF	IP65/68	/	3M tape Clips	5000xD25mm
HLLED-NE-60W-RGBW	SMD	RGBW	24	60W	2000	80	24V 2A	WIFI/RF	IP65/68	/	3M tape Clips	5000xD25mm

Neon Flex shapeable



Features

- 5V USB powered.
- Flexible in any shape.
- Dotless and continue light with RGB color or RGB chasing.
- High density and high efficiency.
- RGB Chroma Lighting with 3-side emitting.

Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLED-NE-1W-RGB	SMD	RGB	5V	0.06W	/	80	5V2A	WIFI/RF	IP20	/	3M tape Clips	L1000mm*H14mm*W7mm

Neon Flex shapeable



Features

- DIY your desired shape.
- Dotless and continue light.
- High density and high efficiency.
- Ultra-long available.
- Shaping a variety of stars and trees to light up the outdoor ambiance.

Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLED-NE-48W-RGBCW	SMD	RGBW	24	18W-48W	/	80	24V 2A	RF	IP20	/	3M tape Clips	5000x14x7mm
HLLED-NE-5W-RGB	SMD	RGB	24	5W	/	80	5V 2A	RF	IP20	/	3M tape Clips	5000x14x7mm
HLLED-NE-5W	SMD	1CCT	24	5W	120	80	5V 2A	RF	IP20	/	3M tape Clips	5000x14x7mm

Special Flexible Super Thin Neon Flex



Features

- Super thin size with 7.8mm width and black flexible housing and 2mm height.
- Dynamic vibrant RGB patterns with zero hotspots.
- Easy use and install, with powered by 5V USB.
- Different modes and length are the most suitable choice for your car!



Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLED-SLIM-7.5W-RGBIC	0807	RGBIC	5	7.5W/M	/	/	5V 1A	RF control	IP20	7mm	3M tape	1500(5ft)*8*2mm

PVC Strip Light



Features

- PVC extrusion with customized length, up to 50m length
- Bright Premium Lighting & Energy Saving: pure and uniform lighting without spots or dark dots.
- Durable & Eco-friendly, cuttable in every 50mm.
- IP65 waterproof design.
- Widely Application: suitable for decorating your home, bedroom, bathroom, car frunk, marine, exterior, boat, trucks, motorcycle, tv, desk, mirror, pool, etc.
- CCT changing through inline switch.



Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	L*D(M*mm)
HLLED-STRIP-300W	SMD	2700K-6500K	110V	300W	24000	80	120V	Key color temperature	IP65	50MM	3M tape Clip	50*16

Wall Washer Strip Light



Features

- High lumen with multiple beam angle lens for wall washer purposes.
- Ultra-long available.
- Durable,Eco-friendly and cuttable.
- IP20/IP65/IP68 waterproof design.



Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLED-WALL WASHER-48W	SMD	1CCT	24	18W-48W	/	80	24V 2A	WIFI/RF	IP20/65/68	/	3M tape Clips	5000X20X11mm

Camera TV Strip Light



Features

- Supports 16 million colors.
- With multiple dynamic modes and scene modes.
- Provide a soft RGB background light.
- Suitable for 55-85 inch smart tv.
- Easy mounting and customization.



50,000 HOURS

CRI >90Ra or >90Ra

WiFi

Bluetooth

zigbee

matter

Works with Siri Shortcuts

WORKS WITH alexa

works with the Google Assistant

Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLED-CAMERA-5W	SMD 5050	RGB	12	5	/	/	12V 1.5A	TUYA APP	IP20	/	3M Tape	3800X12X3mm

HDMI TV Strip Light




Features

- Ultra-low latency with HDMI dedicated chip.
- Supports 16 million colors.
- Supports sound pick-up mode to synchronize lighting with ambient sounds.
- Suitable for 55-85 inch smart tv.
- Easy mounting and customization.



Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLED-TV-8W	SMD 5050	RGB	12	8	/	/	12V 4A	APP	IP20	/	3M Tape	5000X12X3mm

Grow Strip Light




Features

- Energy-saving LED, perfect for hydroponic and soil growth and rated for high humidity use;
- With its adjustable spectrum, can switch color spectrums to match the plants growth stage and increase overall yield and with PAR of up to 16PPF.
- Cooler lamp operation retains moisture and prevents plant burn;
- Link up to 6 light strips for a larger growing footprint;
- Easy installation by simply remove the backing stick to a clean, smooth surface.



Bluetooth[®] Wi-Fi[™] 50,000 HOURS CRI >80Ra or >80Rs														
Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension	PPE	PPF	Dimension
HLLED-GROW -11W	2835	/	120	11W/M	/	24V 1A	RF control	IP44	500mm	3M tape Clip	1000mm*10mm	1.56	13	5mx12mmx3mm

Ultrathin Chasing Color Strip Light



Features

- Ultrathin Design: perfect for car trims and visible edges.
- Syncs to Music: adjust with remote or smart APP.
- Dynamic Lighting: chasing patterns and vibrant colors.
- Easy Installation & Stable Adhesive PC light strip.



Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLED-STRIP-7.5W-RGB	SMD	RGB	5V	7.5W	/	/	/	RF control	IP20	/	double-sided tape	1.5mx-3mmx8mm
HLLED-STRIP-10W-RGB	SMD	RGB	5V	10W	/	/	/	WIFI control	IP20	/	double-sided tape	1.5mx-3mmx8mm

High-voltage input Tape Light



Features

- Super bright and can be used directly by plugging into the AC100V-240V household power supply, and the end will not be dim due to voltage drop.
- Weatherproof with IP65 or IP68 production, which suitable for outdoor work or indoor usage.
- Can be easily folded and installed in the corner. It can also be bent and wrapped around a tree trunk.
- Cuttable: LED strip has a cutting point, which can divide the light strip into many sections.



Model	Power Supply	Power(W)	LED Strip length(m)	LED Qty(pcs)	Luminous Flux(Lm)	CRI (Ra)	CCT (K)	Control Type	Dimension
HLLED-HV TAPE-18W-CW	100-240V 50/60HZ	18	2	352	1500	90	2700K	IR/RF/wifi/BLE	50mx14x6mm
HLLED-HV TAPE-24W-CW	100-240V 50/60HZ	24	3	352	2200	90	2700K-6500K	IR/RF/wifi/BLE	50mx14x6mm
HLLED-HV TAPE-18W-RGBCW	100-240V 50/60HZ	18	2	544	1500	90	2700-6500RGB	IR/RF/wifi/BLE	50mx14x8mm
HLLED-HV TAPE-24W-RGBCW	100-240V 50/60HZ	24	3	544	2200	90	2700-6500RGB	IR/RF/wifi/BLE	50mx14x8mm

High-voltage input COB Light



Features

- COB Lights Waterproof with IP65/68.
- Easy to install, Plug and Play. Input directly with local power at AC100~240V.
- Connectable with end to end with their own connectors, no additional connectors are needed to get longer rope lights, easy and convenient to operate.
- Wide range of applications, decorative rope lighting for Christmas, parties, weddings. You can DIY various styles of indoor bedroom, outdoor camping, patio, deck, pool, landscape, garden, restaurant, club, bar, fence, porch.



Model	Power Supply	Power(W)	LED Strip length(m)	LED Qty(pcs)	Luminous Flux(Lm)	CRI (Ra)	CCT (K)	Control Type	Dimension
HLLED-HV COB-18W-CW	100-240V 50/60HZ	18	2	352	1500	90	2700K	IR/RF/wifi/BLE	2mx10mmx3mm
HLLED-HV COB-24W-CW	100-240V 50/60HZ	24	3	352	2200	90	2700K-6500K	IR/RF/wifi/BLE	3mx10mmx3mm
HLLED-HV COB-18W-RGBCW	100-240V 50/60HZ	18	2	544	1500	90	2700-6500RGB	IR/RF/wifi/BLE	2mx10mmx3mm
HLLED-HV COB-24W-RGBCW	100-240V 50/60HZ	24	3	544	2200	90	2700-6500RGB	IR/RF/wifi/BLE	3mx10mmx3mm

High-voltage input Rope Light




Features

- PVC extrusion process.
- Outdoor Rope Lights Waterproof with IP65. The rope light has thick transparent plastic tube, strong elasticity, anti-UV, energy saving, safe and durable, very suitable for long-term indoor or outdoor use;
- Easy to install, Plug and Play. Input directly with local power at AC100~240V.
- Connectable with end to end with their own connectors, no additional connectors are needed to get longer rope lights, easy and convenient to operate.
- Wide range of applications, decorative rope lighting for Christmas, parties, weddings. You can DIY various styles of indoor bedroom, outdoor camping, patio, deck, pool, landscape, garden, restaurant, club, bar, fence, porch.



Model	Power Supply	Power(W)	LED Strip length(m)	LED Qty(pcs)	Luminous Flux(Lm)	CRI (Ra)	CCT (K)	Control Type	Dimension
HLLED-HV ROPE-18W-CW	100-240V 50/60HZ	18	2	352	1500	90	2700K	IR/RF/wifi/BLE	50mx16mm
HLLED-HV ROPE-24W-CW	100-240V 50/60HZ	24	3	352	2200	90	2700K~6500K	IR/RF/wifi/BLE	50mx16mm
HLLED-HV ROPE-18W-RGBCW	100-240V 50/60HZ	18	2	544	1500	90	2700K+RGB	IR/RF/wifi/BLE	50mx16mm
HLLED-HV ROPE-24W-RGBCW	100-240V 50/60HZ	24	3	544	2200	90	2700-6500K+RGB	IR/RF/wifi/BLE	50mx16mm

High-voltage input Neon COB



Features

- Flexible PVC material, electrical insulation, Fire rating V-0;
- Self-encapsulated design offer four optional white light from different color temperature 2700K~6500K
- High quality FPC;
- Light source lifetime: 50000 hours.
- Min. Bending Diameter: $\Phi 150\text{mm}$ (0.5FT).
- Max. length(M): 30.48M(100FT).

50,000
HOURS

CRI
≥80Ra or ≥90Ra

Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLED-NE-9.5W	COB	2700~6500K	100~240V	9.5W/M	780	90	120~240V	RF control	IP65	305MM	3M tape	5000*16*16mm

High-voltage input Neon Flex



Features

- Easy to install, Plug and Play. Input directly with local power at AC100~240V.
- Dotless and continue light.
- High density and high efficiency.
- Wide Application for indoor and outdoor usage.
- IP67 waterproof design with silicon coating



Type	LED Type	Color(K)	Volt(V)	Watt(W)	Luminous Flux(Lm)	Rendering Index (Ra)	PSU/ Converter	Way of control	IP	Cutting Unit	Installation	Dimension
HLLED-NE-8W	SMD	1CCT R/G/B/Y	100~240V	8W	/	80	100~240V	/	IP67	14MM*7MM	3M tape Clips	5000X6X12mm
HLLED-NE-12W	SMD	1CCT R/G/B/Y	100~240V	12W	/	80	100~240V	/	IP67	14MM*7MM	3M tape Clips	5000X6X12mm
HLLED-NE-14W	SMD	1CCT R/G/B/Y	100~240V	14W	/	80	100~240V	/	IP67	14MM*7MM	3M tape Clips	5000X6X12mm

Christmas String Light



Features

- Available in multiple lengths and with various number of bulbs.
- Each bulb/zone can be customized in colors.
- IP65 waterproof design.
- Easy to DIY: Flexible and cuttable strings with strong adhesive tape, makes easy to bend angle to install and decorate.
- App-controlled or remote controlled, addressable LEDs are designed for extraordinary brightness and color quality in over 16 million colors.
- Perfect for use both indoors and outdoors.




Type	LED TYPE	Color(K)	Voltage (V)	Lengthy	Base Qty	Watt (W)	PSU/ Converter	Way of control	IP	Linking Qty	Dimension
Christmas String Light-A	/	RGBIC	24V	10m/20m/25m/40m/50m	100/200/250/400/500	/	DC24V/1A DC24V/1.5A	WIFI/RF/BLE	IP65	500LEDS/50m	D5mmxH8mm
Christmas String Light-B	/	RGBICW	24V	5m	100	/	DC24V/1A	WIFI/BLE	IP65	/	D5mmxH8mm

Curtain String light



Features

- App-controlled, addressable LEDs were designed for extraordinary brightness and color quality in over 16 million colors.
- Perfect for use both indoors and outdoors.
- IP65 waterproof design.




Type	LED TYPE	Color(K)	Voltage (V)	Lengthy	Base Qty	Watt (W)	Luminous Flux(Lm)	PSU/ Converter	Way of control	IP	Linking Qty
Curtain strip light-A	/	RGBIC	24V	2mx2m	500	/	/	DC24V/10w	WIFI/BLE	IP65	400LEDS
Curtain strip light-B	/	RGB	5V	2mx2m	500	10W	/	DC5V/10w	WIFI/BLE	IP65	400LEDS

String Light



Features

- Goodbye old-school string light,
- Hello ultra futuristic 'envy-of-your-friends' vibe setting outdoor lighting.
- Create hypnotic effects to suit the moment, from shifting sunsets or rolling rainbows to gently flowing icy whites-or just set and forget with easy routines.
- IP65 waterproof design.



Type	LED TYPE	Color(K)	Voltage (V)	Lengthy	Base Qty	Watt (W)	Luminous Flux(Lm)	PSU/ Converter	Way of control	IP	Dimension
HLLED-STRING-60W	G40	3500K /RGB	120V	24/48FT	/	60W	/	24/2A	WIFI/BLE	IP65	D63mm L10730mm

Camping String Light



Features

- Available in multiple lengths.
- USB rechargeable.
- Waterproof camping lanterns Portable LED tent lights.
- Multifunctional Camping Light:suitable not only for decorating camping tents but also yards, RVs, and major holidays, creating various romantic atmospheres.
- Different length are available.

50,000 HOURS CRI >80Ra 90>90Ra WiFi Bluetooth zigbee matter Works with Siri Shortcuts WORKS WITH alexa works with the Google Assistant											
Type	LED TYPE	Color(K)	Voltage (V)	Lengthy	Base Qty	Watt (W)	Luminous Flux(Lm)	PSU/ Converter	Way of control	IP	Linking Qty
New camping light string	2835	RGB	/	24.5ft,29.5ft, 30ft,32ft,34ft ,40ft	/	/	/	/	PIR	IP65	/

Fairy String Light



Features

- Powered by 120V/230V.
- Transform Your Space: This string lights glow a warm/RGB light and create a cozy/colorful ambiance.
- Easy installation & Durable: Easy for you to hang or mount to anywhere in different ways and will endure for years around.
- Different length are available.

50,000
HOURS

CRI
80Ra or 90Ra

Model Numbers	LED TYPE	CCT(K)	Voltage(V)	Lengthy	Base Qty	Watt(W)	PSU/ Converter	Way of control	IP
Fairy String Light	G40	2200K/ 2700K	120/230V	25FT/30FT/50FT	25/30/50	0.7W/bulb	120/230V	Wire control	IP44
Fairy String Light	G40	RGB	120/230V	25FT/30FT/50FT	25/30/50	0.7W/bulb	120/230V	Wire control	IP44

Smart String Light



Features

- Smart control for easy and cosy life.
- Commercial Grade & Shatterproof: Designed with IP65 rating flexible cable.
- Transform Your Space: This Shatterproof outdoor string lights glows RGB light and create a color ful ambiance.
- Easy installation & Durable: Easy for you to hang or mount to anywhere in different ways and will endure for years around.
- Different length are available.



Model Numbers	LED TYPE	CCT(K)	Voltage(V)	Lengthy	Base Qty	Watt(W)	PSU/ Converter	Way of control	IP
Smart String Light	S14	RGB	12	24/48FT	10/15/24	2/3/5	12V 5W	WIFI/BLE	IP65
Smart String Light	S14	RGB	12	48FT/CUSTOMIZED	10/15/24	2/3/5	12V 5W	WIFI/BLE	IP65

Black Translucent String Light



Features

- Several Mode: Three lighting modes for different applications - light bulbs only, embedded light only, light bulbs + embedded lights.
 - Commercial Grade & Shatterproof: Designed with IP65 rating flexible cable.
 - Transform Your Space: This Shatterproof outdoor string lights glows a warm light and create a cozy ambiance.
 - Easy installation & Durable: Easy for you to hang or mount to anywhere in different ways and will endure for years around.
 - PSU: Powered by adapter or solar panel.
- Different length are available.



Model Numbers	LED TYPE	CCT(K)	Voltage(V)	Lengthy	Base Qty	Watt(W)	PSU/ Converter	Way of control	IP
Black Translucent String Light	S14	2200K/ 2700K	120V/230V	24FT/48FT	12/24	0.5~2W/bulb	120V/230V	Remote control Wire control	IP65
Black Translucent String Light	S14	2200K/ 2700K	5V	24FT/48FT	12/24	0.5~2W/bulb	5V/Solar	Remote control Wire control	IP65

Solar String Light



Features

- Smart control for easy and cosy life
- Commercial Grade & Shatterproof: Designed with IP65 rating flexible cable.
- Transform Your Space: This Shatterproof outdoor string lights glows RGB light and create a color ful ambiance.
- Easy installation & Durable: Easy for you to hang or mount to anywhere in different ways and will endure for years around.
- Different length are available.

50,000
HOURS

CRI
80Ra 90Ra

Model Numbers	LED TYPE	CCT(K)	Voltage(V)	Lengthy	Base Qty	Watt(W)	PSU/ Converter	Way of control	IP
Solar String Light	S14	2200K/ 2700K	5V	24FT/48FT	12/24	0.5~2W/bulb	5V 3W	Solar	IP65
Solar String Light	S14	2200K/ 2700K	5V	24FT/48FT	12/24	0.5~2W/bulb	5V 3W	Solar	IP65
Solar String Light	S14	RGB	5V	24FT/48FT	12/24	0.5~2W/bulb	5V 3W	Solar	IP65

Classic String Light



Features

- Powered by 120V/230V
- Commercial Grade & Shatterproof: Designed with IP65 rating flexible cable.
- Transform Your Space: This Shatterproof outdoor string lights glows a warm/RGB light and create a cozy/colorful ambiance.
- Easy installation & Durable: Easy for you to hang or mount to anywhere in different ways and will endure for years around.
- Different length are available.



Model Numbers	LED TYPE	CCT(K)	Voltage(V)	Lengthy	Base Qty	Watt(W)	PSU/ Converter	Way of control	IP
Classic String Light	S14	2200K/ 2700K	120V/230V	24FT/48FT	12/24	0.5~2W/bulb	120V/230V	Wire control	IP65
Classic String Light	S14	2200K/ 2700K	120V/230V	24FT/48FT	12/24	0.5~2W/bulb	120V/230V	Wire control	IP65
Classic String Light	S14	RGB	120V/230V	24FT/48FT	12/24	0.5~2W/bulb	120V/230V	Wire control	IP65

Indoor String Light



Features

- Powered by 120V/230V.
- Transform Your Space: This string lights glow a warm/RGB light and create a cozy/colorful ambiance.
- Easy installation & Durable: Easy for you to hang or mount to anywhere in different ways and will endure for years around.
- Different length are available.



Model Numbers	LED TYPE	CCT(K)	Voltage(V)	Lengthy	Base Qty	Watt(W)	PSU/ Converter	Way of control	IP
Indoor String Light	G40	2200K/ 2700K	120V/230V	25FT/50FT/100FT	25/50/100	0.7W/bulb	120V/230V	Wire control	IP44
Indoor String Light	ST38	2200K/ 2700K	120V/230V	25FT/50FT/100FT	25/50/100	0.7W/bulb	120V/230V	Wire control	IP44
Indoor String Light	G40	RGB	120V/230V	25FT/50FT/100FT	25/50/100	0.7W/bulb	120V/230V	Wire control	IP44

